



DC-AC Inverter
⚡ Pure Sine Wave

Model
PST-600-48
 48 VDC - 120 VAC

Design Features

- High efficiency
- 166% Surge Power
- Temperature controlled cooling fan – reduces energy consumption
- Low RF emissions
- Wide operating DC input range: 42.0 - 64.0 VDC
- Commercial grade design suitable for heavy duty loads, long periods of continuous operation & for emergency back up
- UPC – Universal Protection Circuit: low voltage, over voltage, over temperature, over load and short circuit.
- Low idle power draw
- Duplex GFCI protected AC outlets
- Optional remote control (sold separately): Model RC-15A
- Meets UL & CSA Standards, FCC compliant

3 YEAR LIMITED WARRANTY



	MODEL NO.	PST-600-48
OUTPUT	OUTPUT VOLTAGE	120 VAC ± 3%
	MAXIMUM OUTPUT CURRENT	5.1A
	OUTPUT FREQUENCY	60 Hz ± 1%
	TYPE OF OUTPUT WAVEFORM	Pure Sine Wave
	TOTAL HARMONIC DISTORTION OF OUTPUT WAVEFORM	< 3%
	CONTINUOUS OUTPUT POWER (At Power Factor = 1)	600 Watts
	SURGE OUTPUT POWER	1000 Watts (< 8 ms)
	PEAK EFFICIENCY	90%
INPUT	AC OUTPUT CONNECTIONS	NEMA5-20R GFCI Duplex Receptacle
	NOMINAL DC INPUT VOLTAGE	48 VDC
	DC INPUT VOLTAGE RANGE	42.0 - 64.0 VDC
	MAXIMUM INPUT CURRENT	20A
	DC INPUT CURRENT AT NO LOAD	< 0.3A
DISPLAY	DC INPUT CONNECTIONS	Bolt & Nut: 5/16" x 18 TPI
	DC INPUT FUSES (INTERNAL)	2 x 10A = 20A (Each 10A, 58V, Blade Type)
PROTECTIONS	LED	Power, Overload, Over Temperature
	LOW DC INPUT VOLTAGE ALARM	42.0V ± 0.5V
	LOW DC INPUT VOLTAGE SHUTDOWN	40.0 ± 0.5 VDC ; Auto-reset: 46.0 ± 0.5 VDC
	HIGH DC INPUT VOLTAGE SHUTDOWN	64.0 VDC ; Auto-reset: < 64.0 VDC
	SHORT CIRCUIT SHUTDOWN	When output voltage drops to 80 VAC or lower for 1 to 1.5 sec
	OVERLOAD SHUTDOWN	At overload of 110% to 115% for 2 to 2.5 sec
	GROUND FAULT SHUTDOWN	Through GFCI outlets (5 to 6 mA leakage)
REMOTE	OVER TEMPERATURE SHUTDOWN	90°C ± 5°C (Sensed at internal hot spot) ; Auto reset at 65°C ± 5°C
	REVERSE POLARITY ON DC INPUT SIDE	External / internal DC sides fuses will blow
COOLING	WIRED REMOTE CONTROL WITH LED DISPLAY	RC-15A with 5m / 16.5 ft cable (sold separately)
COMPLIANCE	FORCED AIR COOLING	1 Temperature controlled fan (Temperature is sensed at internal hot spot ; Fan ON at 55°C ÷ 3°C ; Fan OFF at 45°C ± 3°C)
	SAFETY	Meets UL Standard UL 60950-1 and CSA Standard C22-2 No.107.1-01 for Information Technology Equipment
ENVIRONMENT	EMI / EMC	FCC Part 15(B), Class B
	OPERATING TEMPERATURE RANGE	Operating temperature -20 to 40°C / -4 to 104°F Storage temperature -30 to 70°C / -22 to 158°F 90% relative humidity non-condensing
DIMENSIONS	(W X D X H), MM	238 x 276.2 x 82
	(W X D X H), INCHES	9.37 x 10.87 x 3.23
WEIGHT	KG / LBS	2.7 / 5.9

NOTES:

1. All power ratings are specified for resistive load at Power Factor = 1.
2. All specifications given above are at ambient temperature of 25°C / 77°F.
3. Specifications are subject to change without notice

12001-PST-600-48-1119